

SECTION 305 GRADED AGGREGATE FOR TEMPORARY ROADWAY MATERIAL (TRM)

305.01 Description. This work consists of furnishing and placing graded aggregate as temporary roadway material (TRM) for the maintenance and repair of the roadway, for pipe and utility crossings, for driveways and entrances, for temporary ramps up to curbs, and for other areas as directed by the Engineer. TRM under this Section shall not be used for constructing detour roads or other temporary roadways; however, it can be used for their maintenance.

305.02 Materials. Graded aggregate for TRM shall conform to the requirements of [Section 821](#), Type B.

305.03 Construction Methods. Repair of the existing pavement and the placement of TRM shall be done as approved or directed by the Engineer. The work shall be coordinated with all other work and operations necessary to maintain traffic.

305.04 Method of Measurement. The quantity of graded aggregate for TRM will be measured as the actual number of tons (metric tons) of graded aggregate placed and accepted. The weight will be determined according to [Subsection 109.01](#).

305.05 Basis of Payment. The quantity of graded aggregate for TRM will be paid for at the Contract unit price per ton (metric ton). Price and payment will constitute full compensation for furnishing, preparing, hauling, placing and compacting all materials; for disposal of temporary roadway material; and for all labor, equipment, tools and incidentals required to complete the work.

[Back to Top](#)