

SECTION 751 ADJUSTING FIRE HYDRANTS

751.01 Description. This work consists of adjusting fire hydrants.

751.02 Materials. Materials for adjusting fire hydrants shall conform to the following Sections:

Backfill Material, Borrow Type C	209
Portland Cement Concrete, Class B	812
Stone, Delaware No. 8	813

All pipe, fittings, and hardware shall conform to the requirements shown on the Plans and to the standards and specifications of the utility owner.

751.03 Construction Methods. Fire hydrants shall be adjusted in accordance with the details shown on the Plans and the standards and specifications of the utility owner, and as directed by the Engineer. The Contractor shall acquaint itself with these standards and specifications prior to the submission of a proposal for the construction of the work included in the Contract documents. The location of the fire hydrants shall be as shown on the Plans, but the exact position of the adjusted hydrants shall be determined in the field.

751.04 Method of Measurement. The quantity of fire hydrants adjusted will be measured as the actual number of fire hydrants adjusted and accepted.

751.05 Basis of Payment. The quantity of fire hydrants adjusted will be paid for at the Contract unit price per each. Price and payment will constitute full compensation for all materials, including concrete, stone, and any contingent materials relative and necessary to the work; for all excavating, backfilling, testing, compacting, and disposing of excess material; and for all labor, equipment, tools, and incidentals required to complete the work.

Any valves, fittings, connections, or joints determined by the Engineer to be unsuitable for reuse shall be replaced at the Contractor's expense.