

SECTION 753 ADJUSTING SANITARY SEWER LATERALS

753.01 Description. This work consists of adjusting sewer connections that interfere with the proposed construction or which are damaged by unavoidable construction operations.

753.02 Materials. Materials for adjusting sanitary sewer laterals shall conform to the following Sections:

| | |
|-----------------------------------|-----|
| Backfill Material, Borrow Type C | 209 |
| Portland Cement Concrete, Class B | 812 |
| Stone, Delaware No. 8 | 813 |

All pipe, fittings, and hardware shall conform to the requirements shown on the Plans and to the standards and specifications of the utility owner.

753.03 Construction Methods. All sewer connections shall be adjusted in accordance with the details shown on the Plans and the standards and specifications of the utility owner, and as directed by the Engineer. The Contractor shall acquaint itself with these standards and specifications prior to the submission of a proposal for the construction of the work included in the Contract documents. The location of the sewer connections shall be as shown on the Plans.

No lateral changes shall be made without the approval of the Engineer or the Engineer's authorized representative.

All existing sanitary or combined sewers must be retained in service during construction and until acceptance of portions of new replacement facilities. Temporary piping, if necessary, shall be utilized to maintain service during construction. All construction shall be coordinated with and written approval obtained from the utility owner prior to the interruption for temporary connections or new facilities of existing sanitary or combined sewers.

753.04 Method of Measurement. The quantity of sanitary sewer laterals adjusted will be measured as the actual number of laterals adjusted and accepted.

753.05 Basis of Payment. The quantity of sanitary sewer laterals adjusted will be paid for at the unit price per each. Price and payment will constitute full compensation for all necessary excavating, backfilling, compacting, and disposing of excess material; for all cribbing, shoring, and sheeting; for furnishing and installing pipe and fittings regardless of size; for concrete encasement of fittings, regardless of size; for concrete encasement of fittings and joints, if required; and for all material, labor, equipment, tools, and incidentals required to complete the work.