

Add lime, at no additional cost to the Department, to any section on which washing or blowing prior to mixing caused excessive lime loss.

Reconstruct areas, at no cost to the Department, on which lime-treated soil was constructed but not covered with a layer of pavement, base, or other construction material during the same construction season.

The Engineer will test each section as it is completed. Scarify, moisten, rework, and compact any section with a density less than the specified requirements according to the requirements of these Specifications and at no additional cost to the Department.

No payment will be made for lime application exceeding the 10 percent plus tolerance. When the quantity applied is deficient by more than 10 percent, additional lime shall be applied prior to mixing at the Contractor's expense.

## **Section 230—Lump Sum Construction**

### **230.1 General Description**

Specifications for this work will be included elsewhere in the Contract.

## **Section 231—Miscellaneous Construction, Unpaved Roads and Streets**

### **231.1 General Description**

Specifications for this work will be included elsewhere in the Contract.

## **Section 232—Railroad Construction**

### **232.1 General Description**

Specifications for this work will be included elsewhere in the Contract.

## **Section 233—Haul Roads**

### **233.1 General Description**

This work includes maintaining and repairing haul roads that are county roads and city streets within the State of Georgia. Haul roads on the State Highway System are not included.

#### **233.1.01 Definitions**

Haul roads: Routes used for transporting materials to a Project. Haul roads include routes described in the Contract and alternate routes approved by the Engineer.

#### **233.1.02 Related References**

##### **A. Standard Specifications**

Section 109—Measurement and Payment

Section 209—Subgrade Construction

Section 317—Reconstructed Base Course

Section 400—Hot Mix Asphaltic Concrete Construction

Section 412—Bituminous Prime

Section 413—Bituminous Tack Coat

Section 424—Bituminous Surface Treatment