

a pressure distributor in a uniform, continuous spread over the area to be treated and within the temperature range specified in Section 702.05 - Application Temperatures. The rate of application and areas to be treated will be specified in the contract.

When traffic is maintained, one-way passage of vehicles will be maintained on the untreated portion of the roadway. Bituminous tack coat shall not be placed on any surface where traffic will be forced to travel upon the uncovered tack coat. All tack coat shall be covered on the day it is applied.

Care shall be taken so that the application of the bituminous tack coat at the junction of spreads is not in excess of the specified amount. Skipped areas and deficiencies shall be corrected as directed.

409.08 Method of Measurement Unless otherwise specified, bituminous tack coat will be measured by the liter [gallon]. All quantity determinations will be made in accordance with Section 108 - Payment.

409.09 Basis of Payment The accepted quantity of bituminous tack coat will be paid for at the contract unit price per liter [gallon] for the designated type of material complete in place.

Payment will be made under:

<u>Pay Item</u>	<u>Pay Unit</u>
409.15 Bituminous Tack Coat, Applied	liter [gallon]

## SECTION 410 - BITUMINOUS SURFACE TREATMENT

Reserved

## SECTION 411 - UNTREATED AGGREGATE SURFACE COURSE

411.01 Description This work shall consist of constructing a surface course or