

temperature of the concrete to be treated shall be above 4°C [40°F] at the time of application.

515.05 Method of Measurement Protective coating for concrete surfaces will be measured for payment by the square meter [square yard] or lump sum unit as specified, satisfactorily applied and accepted.

515.06 Basis of Payment Protective coating for concrete surfaces will be paid for at the contract unit price per square meter [square yard] or lump sum as specified.

Payment will be made under:

<u>Pay Item</u>	<u>Pay Unit</u>
515.20 Protective Coating for Concrete Surface	square meter [Square Yard]
515.21 Protective Coating for Concrete Surfaces	Lump Sum

SECTION 516 - STYRENE-BUTADIENNE LATEX MODIFIED PORTLAND CEMENT MORTAR AND CONCRETE

Reserved

SECTION 517 - SHOTCRETE

Reserved

SECTION 518 - STRUCTURAL CONCRETE REPAIR

518.01 Description This work shall consist of repairing existing substructure and superstructure structural concrete as shown on the plans and/or as directed by the Resident. Repairing structural concrete shall include removal and disposal of deteriorated concrete, cleaning exposed reinforcing steel by sandblasting and/or wire brushing, and placing repair material. All work shall be in conformance with applicable provisions of Sections 202, 502, and 503. Upward facing surfaces are