

**SECTION 424—BITUMINOUS WEARING COURSE ID-3 (STANDARD),
BITUMINOUS WEARING COURSE ID-3 (HEAVY DUTY),
BITUMINOUS WEARING COURSE ID-3, RPS (STANDARD),
AND BITUMINOUS WEARING COURSE ID-3, RPS (HEAVY DUTY)**

424.1 DESCRIPTION—This work is construction of a wearing course of plant-mixed bituminous concrete on a prepared surface.

424.2 MATERIAL—[Section 420.2](#) with the following modifications:

(d) Mixture Composition.

1. Standard Bituminous Mixtures. [Section 401.2\(e\)](#), except provide a minimum percent VMA (Voids in Mineral Aggregate) of 13.

2. Heavy Duty Bituminous Mixtures. [Section 401.2\(e\)](#), except revise the VMA requirements of ID-2 courses as follows:

Provide a minimum JMF percent VMA of 14 and a minimum plant mixture percent VMA of 13.

424.3 CONSTRUCTION—[Section 420.3](#)

424.4 MEASUREMENT AND PAYMENT—

- (a) Bituminous Wearing Course ID-3 (Standard).** Square Meter (Square Yard) or Tonne (Ton)
- (b) Bituminous Wearing Course ID-3 (Heavy Duty).** Square Meter (Square Yard) or Tonne (Ton)
- (c) Leveling Course (Standard).** Tonne (Ton)
- (d) Leveling Course (Heavy Duty).** Tonne (Ton)
- (e) Bituminous Wearing Course ID-3, RPS (Standard).** Square Meter (Square Yard) or Tonne (Ton)
- (f) Bituminous Wearing Course ID-3, RPS (Heavy Duty).** Square Meter (Square Yard) or Tonne (Ton)