

SECTION 01891

MOVE STREET SIGNS AND MAILBOX ASSEMBLIES

PART 1 GENERAL

1.1 SECTION INCLUDES

- A. Move or reset street signs.
- B. Move or reconstruct existing mailbox supports.

1.2 RELATED SECTIONS

- A. Section 03055: Portland Cement Concrete
- B. Section 06055: Timber and Timber Treatment

1.3 REFERENCES

- A. AASHTO M 111: Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products
- B. ASTM A 36: Carbon Structural Steel

PART 2 PRODUCTS

2.1 CONCRETE

- A. Class B. Refer to Section 03055
- B. Substitute higher class of concrete if desired.

2.2 WOOD POSTS FOR MAILBOX AND SIGN

- A. Refer to Section 06055

2.3 MAILBOX MOUNTING HARDWARE

- A. Shelf, platform, and bracket.
- B. Zinc plated bolts, washers, and nuts.
- C. ASTM A 36M, and AASHTO M 111. Follow GW series Standard Drawings.

PART 3 EXECUTION

3.1 MOVE STREET SIGN

- A. Maintain existing signs until construction requires removal. Coordinate with Engineer 24 hours in advance of removing any sign.
- B. Relocate existing street signs as indicated or as directed by the Engineer.
- C. Remove concrete from existing posts where posts are to be reused.
- D. Reset post in 8.0-inch diameter concrete base. Keep the box within 1/8 inch of the finished grade.
- E. Fill and compact hole left by removing sign post. Compact to density of adjacent material.

3.2 MOVE MAILBOX

- A. Furnish and install new posts, shelf, and brace, firmly attaching boxes to the support. Refer to GW series Standard Drawings.
- B. Repair or replace mailboxes damaged during construction.
- C. Install temporary posts and mailboxes if required, then remove.

END OF SECTION