

**SECTION 02773**

**ASPHALT CONCRETE CURB**

**PART 1 GENERAL**

**1.1 SECTION INCLUDES**

- A. Materials and procedures for constructing asphalt concrete curb.

**1.2 RELATED SECTIONS**

- A. Section 02745: Asphalt Material.
- B. Section 02748: Prime Coat/Tack Coat.

**PART 2 PRODUCTS**

**2.1 ASPHALT CEMENT**

- A. Refer to Section 02745.

**2.2 MINERAL AGGREGATE**

- A. As specified in AASHTO and the following gradation:

<b>Mineral Aggregate Gradation</b>	
<b>Sieve Size</b>	<b>Percent Passing (by weight)</b>
1/2 inch	100
No. 4	50-70
No. 10	30-50
No. 200	5-10

**2.3 TACK COAT**

- A. Refer to Section 02748.

## **PART 3 EXECUTION**

### **3.1 PREPARATION**

- A. Clean existing surface thoroughly.
- B. Place tack coat at 0.06 gal/yd<sup>2</sup> residual asphalt or less.

### **3.2 PLACEMENT**

- A. Use an extrusion machine to place the curb.
- B. Maintain the temperature of the hot mix asphalt as designated by the mix design. Refer to Section 02745.
- C. Finish top and inside face of curb uniformly and free of irregularities.

END OF SECTION